


P.C.B LAYOUT (BOTTOM VIEW)

Tolerance: ±0.05

Electrical schematic



主要技术特性要求:

1. 使用条件:

环境温度: -25~70°C

相对湿度: 90% (40°C)

2. 额定负荷: 30V DC 1.0A

3. 接触电阻: ≤30mΩ

4. 绝缘电阻: ≥100MΩ

5. 耐压: AC500V (50Hz) 1min

6. 插拔力: 5~30N

7. 寿命: 5000次

7	铜套	黄铜H59	1	镀镍		
6	底座	PBT	1	黑色		
5	5#插针	黄铜H62	1	镀锡		
4	2#插针	黄铜H62	1	镀锡		
3	4#插针	磷铜QSn6.5-0.1	1	镀锡		
2	3#插针	磷铜QSn6.5-0.1	1	镀锡		
1	1#插针	黄铜H62	1	镀锡		
序号	零件料号	名称	材料	数量	镀层/颜色	备注



深圳市华宇创精密电子有限公司

TOLERANCE:

X.X ±0.30

X.XX ±0.25

X.XXX ±0.15

X' ±2' X.X' ±0.5'

UNIT: mm [inch]

SCALE:1:1

SIZE: A4

DRAWN BY :

陈一鸣

DATE :

2014-02-23

PART NAME:

6.35 话筒插座5P

CHECKED BY:

马跃

DATE :

2014-02-23

PART NO.

HYC-CK-6.35-630-5P

APPROVED BY:

邱敏

DATE :

2014-02-23

DRAW NO:

HYC-2405281708

SHEET NO.

1 OF 1