



主要技术性能	
额定电负荷	DC 30V\0.5A
接触电阻	≤0.03Ω
绝缘电阻	≥100MΩ
耐压	AC500V(50Hz)/min
插拔力	3-20N
使用温度范围	-30-70℃
使用寿命	5000次



6						
5	DC-005K-05	后盖	1	PBT(白色)		
4	DC-005K-04	底座	1	PBT(白色)		
3	DC-005K-03	弹片	1	磷铜	0.3T	镀银
2	DC-005K-02	弯钩	1	黄铜	0.4T	镀银
1	DC-005K-01	圆针	1	黄铜		镀银
序号	产品编号	产品名称	数量	材料	规格	电镀



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: DC-005K
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HVC-DC005K-200
 UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HVC-2407271953
			SHEET NO. 1 OF 1