


主要技术性能

1. 额定电负荷: 30V 0.5A;
2. 接触电阻: $\leq 0.03 \Omega$;
3. 绝缘电阻: $\geq 100M \Omega$;
4. 耐压: AC500V (50Hz)/min;
5. 插拔力: 3~20N;
6. 寿命: 5,000次。

序号	名称	数量	材料	备注
5	平片	1	H62(Y)黄铜带 $\delta=0.3mm$	铜锡
4	插针	1	H62黄铜棒	铜锡
3	弯片	1	H62(Y)黄铜带 $\delta=0.3mm$	铜锡
2	簧片	1	QSn6.5-0.1(Y)锡青铜带 $\delta=0.25mm$	锡铈
1	底座	1	PPA	黑

电路原理图



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ± 0.30 X.XX ± 0.25 X.XXX ± 0.15 X.' $\pm 2'$ X.X' $\pm 0.5'$	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: DC-006D	
	CHECKED BY : 马跃	DATE : 2014-02-23	PART NO. HVC-DC006D-165	MOLD NO.
UNIT: mm [inch] SCALE: 1:1 SIZE: A4	APPROVED BY : 邱国夷	DATE : 2014-02-23	DRAW NO: HVC-DC16060217	SHEET NO. 1 OF 1