


电路板开孔尺寸
TOP VIEW

技术特性:

使用条件: $-30\sim 70^{\circ}$
 额定负荷: DC30V 0.5A
 接触电阻: $\leq 0.03\ \Omega$
 绝缘电阻: $\geq 100M\ \Omega$ DC250V
 耐压: AC500V (50Hz)/min
 插入力: 3~20N
 拔出力: 8~15N
 寿命: 5000次

6	插 针	1	H59黄铜棒	D. Cu/Sn
5	平 片	1	H62黄铜带(Y) $\delta=0.30\text{mm}$	D. Cu/Sn
4	弯 片	1	H62黄铜带(Y) $\delta=0.35\text{mm}$	D. Cu/Sn
3	簧 片	1	H65磷铜带(Y) $\delta=0.25\text{mm}$	D. Sn
2	后 盖	1	PBT 工程塑料	黑
1	基 座	1	PBT 工程塑料	黑
序号	名称	数量	材 料	备注

电路原理图



孔径 (θA)	针直径 (θB)
4	1.1
4	1.3
6.3	2.0
6.3	2.5

深圳市华宇创精密电子有限公司

TOLERANCE: X.X ± 0.30 X.XX ± 0.25 X.XXX ± 0.15 X' $\pm 2'$ X.X' $\pm 0.5'$ UNIT: mm [inch] SCALE: 1:1 SIZE: A4	DRAWN BY:	DATE:	PART NAME:
	陈一鸣	2014-02-23	DC-012B
	CHECKED BY:	DATE:	PART NO.
	马跃	2014-02-23	HVC-DC012B-XXX
APPROVED BY:	DATE:	DRAW NO.	MOLD NO.
邱敏	2014-02-23	HVC-1907081628	
		SHEET NO.	1 OF 1