


技术要求

使用条件: -40 ~ 55°C
 额定负荷: DC 30V 2A
 接触电阻: ≤ 0.03Ω
 绝缘电阻: ≥ 100MΩ DC250V
 耐压: AC 500V (50Hz)/min
 插拔力: 3 ~ 20N
 机械寿命: 5000次

TOLERANCE: UNLESS OTHERWISE SPECIFIED		
UNOER 1.5 ± 0.03	1.5 ~ 10 ± 0.1	OVER 10 ± 0.2

电路结构示意图




7		螺帽	1PCS	H59-1黄铜	电渡: 镍
6		盖板	1PCS	酚醛纸板T=1.6	颜色: 黄色
5		底座	1PCS	PA 66	颜色: 黑色
4		插针	1PCS	H59-1黄铜 φ=2.0	电渡: 锡
3		静触片	1PCS	H62 黄铜 t=0.30	电渡: 银
2		动触片	1PCS	65Mn钢 t=0.20	电渡: 银
1		插针脚	1PCS	H62 黄铜 t=0.30	电渡: 银
序号	零件图号或代号	名称	数量	材料	备注



深圳市华宇创精密电子有限公司

TOLERANCE:
 X.X ±0.30
 X.XX ±0.25
 X.XXX ±0.15
 X' ±2' X.X' ±0.5'



UNIT: mm [inch]
 SCALE: 1:1 SIZE: A4

DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: DC-022	
CHECKED BY : 马跃	DATE : 2014-02-23	PART NO.	HYC-DC022-200
APPROVED BY : 柯南	DATE : 2014-02-23	MOLD NO.	
		DRAW NO:	HYC-DC2020032733
		SHEET NO.	1 OF 1