





主要技术性能	
额定电负荷	DC 30V/0.5A
接触电阻	≤0.03Ω
绝缘电阻	≥100MΩ
耐压	AC500V(50Hz)/min
插拔力	3-20N
使用温度范围	-30-70℃
使用寿命	5000次




P. C. B LAYOUT TOP VIEW



5	DC-033-05	圆针	1	黄铜		镀银
4	DC-033-04	插片	1	黄铜	0.25T	镀银
3	DC-033-03	平片	1	黄铜	0.3T	镀银
2	DC-033-02	弹片	1	磷铜	0.3T	镀银
1	DC-033-01	底座	1	PPA(黑色)		
序号	产品编号	产品名称	数量	材料	规格	电镀


深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: DC-033	
	CHECKED BY : 马跃	DATE : 2014-02-23	PART NO. HYC-DC033-130	MOLD NO.
 UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY : 邱敏	DATE : 2014-02-23	DRAW NO: HYC-2404112012	SHEET NO. 1 OF 1