

NOTES:

- 1.ELECTRIC CHARACTERISTICS:
 - 1-1.CONTACT CURRENT RATING: 4A.
 - 1-2.CONTACT VOLTAGE RATING: 20V DC.
 - 1-3.CONTACT RESISTANCE: 30mΩ MAX.;
 - 1-4.DIELECTRIC WITHSTANDING VOLTAGE: 500V AC;
 - 1-5.INSULATION RESISTANCE: 100MΩ MIN.AT DC 500V.
- 2.MECHANICAL CHARACTERISTICS:
 - 2-1.DURABILITY:3000 CYCLES.
 - 2-2.INSERTION AND EXTRACTION FORCE:
 - 2-2.1.INSERTION FORCE: 30N MAX.
 - 2-2.2.EXTRACTION FORCE: 3N MIN.
- 3.ENVIRONMENT CHARACTERISTICS:
 - 3-1.OPERATING TEMPERATURE: -25℃~+85℃.
 - 3-2.HUMIDTY:45~85% RH.

5	底座	1	LCP	BLACK
4	盖脚	1	磷铜 T=0.2mm	Ag PLATED
3	开关弹片	1	黄铜 T=0.25mm	Ag PLATED
2	开关弹片	1	磷铜 T=0.3mm	Ag PLATED
1	电极中心柱	1	黄铜	CuSn PLATED
NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR




深圳市华宇创精密电子有限公司

TOLERANCE:

X.X ±0.30
X.XX ±0.25
X.XXX ±0.15

X' ±2' X.X' ±0.5'



UNIT: mm [inch]

SCALE:1:1 SIZE: A4

DRAWN BY :

陈一鸣

DATE :

2014-02-23

PART NAME:

DC-037

CHECKED BY:

马跃

DATE :

2014-02-23

PART NO.

HYC-DC037-145

MOLD NO.

APPROVED BY:

邱敏

DATE :

2014-02-23

DRAW NO:

HYC-2403041836

SHEET NO.

1 OF 1