


线路板安装示意图

技术要求

使用条件: -40~55℃
 额定负荷: DC 30V 0.5A
 接触电阻: < 0.03Ω
 绝缘电阻: > 100MΩ DC250V
 耐压: AC 500V(50Hz)/min
 插拔力: 3~20N
 机械寿命: 5000次

电路结构示意图



4	底座	1PCS	PBT (黑色)			
3	静触片	1PCS	H62 黄铜 t=0.50	电镀: 银		
2	动触片	1PCS	磷铜 t=0.25	电镀: 银		
1	插针脚	1PCS	H62 黄铜 t=0.50	电镀: 银		
序号	零件图号或代号	名称	数量	材料	镀层	备注



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: DC-038 大孔
	CHECKED BY : 马跃	DATE : 2014-02-23	PART NO. : HYC-DC038-150
UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY : 邱国夷	DATE : 2014-02-23	DRAW NO: HYC-DC17091214 SHEET NO. 1 OF 1