



P. C. B LAYOUT TOP VIEW



主要技术性能	
额定负荷	DC 30V\0.5A
接触电阻	≤0.03Ω
绝缘电阻	≥100MΩ
耐压	AC500V(50Hz)/min
插拔力	3-20N
使用温度范围	-30-70℃
使用寿命	5000次

6	DC-041-06	盖脚	1	黄铜	0.2T	镀银
5	DC-041-05	插片脚	1	黄铜	0.25T	镀银
4	DC-041-04	弹片脚	1	磷铜	0.25T	镀银
3	DC-041-03	后脚	1	磷铜	0.2T	镀银
2	DC-041-02	圆针	1	黄铜		镀银
1	DC-041-01	底座	1	PPA		黑色
序号	产品编号	产品名称	数量	材料	规格	处理



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: DC-041 无柱
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. : HYC-DC041C-060
 UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO. : HYC-2201151556
			SHEET NO. : 1 OF 1