



PIN	ø2.0	ø2.5
-----	------	------

主要技术性能	
额定电负荷	DC 30V\3A
接触电阻	≤0.03Ω
绝缘电阻	≥100MΩ
耐压	AC500V (50Hz)/min
插拔力	3-30N
使用温度范围	-30-70℃
使用寿命	5000次

序号	产品编号	产品名称	数量	材料	规格	处理
5	DC-044-05	弹片脚	1	锰钢	0.25	铜锡
4	DC-044-04	插片脚	1	黄铜	0.3T	铜锡
3	DC-044-03	平片	1	黄铜	0.3T	铜锡
2	DC-044-02	圆针	1	黄铜		铜锡
1	DC-044-01	底座	1	PPA		黑色



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: DC-044
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC02-DC044-XXX MOLD NO.
	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HYC-2307061726 SHEET NO. 1 OF 1
SCALE:1:1 SIZE: A4			

P. C. B LAYOUT TOP VIEW