


P. C. B LAYOUT
TOP VIEW

SCHMATIC



PIN	$\phi 2.0$	$\phi 2.5$
APPD.		

SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance: $\leq 0.03 \Omega$;
3. Insulation resistance: $\geq 100M \Omega$ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. life test: 5,000 cycles.

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
6	PIN	1	H62 BRASS (ROHS)	Sn-Plating (ROHS)
5	CURVE PIECE	1	H62 BRASS (ROHS)	Ag-Plating (ROHS)
4	SPRING PIECE	1	C5191 (ROHS)	Ag-Plating (ROHS)
3	FLAT PIECE	1	H62 BRASS (ROHS)	Ag-Plating (ROHS)
2	COVER	1	PPA (ROHS)	
1	HOUSING	1	PPA (ROHS)	



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ± 0.30 X.XX ± 0.25 X.XXX ± 0.15 X.' $\pm 2'$ X.X' $\pm 0.5'$	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: DC-050A
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HVC-DC050A-XXX
	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HVC-2503241001
SCALE: 1:1 SIZE: A4			SHEET NO. 1 OF 1