


印制电路板开孔尺寸



接点示意图

主要技术特性:

1. 额定电负荷: 50V, 0.2A;
2. 接触电阻:  $\leq 0.03 \Omega$ ;
3. 绝缘电阻:  $\geq 100 \Omega$ ;
4. 耐压: AC500V (50HZ) 1min;
5. 插拔力: 3-20N;
6. 寿命: 5,000次。

6	后盖	1	酚醋层压板T=1.20	
5	底座	1	PBT	(黑)
4	插针	1	H59黄铜棒	铜锡
3	簧片	1	65磷铜带T=0.25	锡铈
2	弯片	1	H62黄铜带T=0.30	铜锡
1	平片	1	H62黄铜带T=0.30	铜锡
序号	名称	数量	材料	镀涂



深圳市华宇创精密电子有限公司

TOLERANCE:

X.X  $\pm 0.30$   
 X.XX  $\pm 0.25$   
 X.XXX  $\pm 0.15$   
 X'  $\pm 2'$  X.X'  $\pm 0.5'$

UNIT: mm [inch]

SCALE: 1:1 SIZE: A4

DRAWN BY:

陈一鸣

DATE:

2014-02-23

PART NAME:

DC-052C

CHECKED BY:

马跃

DATE:

2014-02-23

PART NO.:

HYC-DC052C-130

MOLD NO.:

APPROVED BY:

邱敏

DATE:

2014-02-23

DRAW NO.:

HYC-2011131219

SHEET NO.:

1 OF 1