



技术要求

- 1、插入力: 5~8N(0.3~3.0kgf)
- 2、拔出力: 5~8N(0.3~3.0kgf)
- 3、接触电阻: $\leq 30m\Omega$
- 4、绝缘电阻: $>100M\Omega$ DC 500V
- 5、耐电压: AC 500V 1min无飞弧及击穿
- 6、寿命: 10000 10~20次/min
- 7、额定负载: DC 12V 1A
- 8、适用温度范围: $-25 \sim 85^\circ C$
- 9、推荐使用插头:



P.C.B LAYOUT TOP VIEW

 深圳市华宇创精密电子有限公司			
TOLERANCE: X.X ± 0.30 X.XX ± 0.25 X.XXX ± 0.15 X.' $\pm 2'$ X.X' $\pm 0.5'$	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: DC-055C
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC-DC055C-065
  UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱国夷	DATE : 2014-02-23	PART NO. HYC-DC13052401
			DRAW NO: HYC-DC13052401
			SHEET NO. 1 OF 1