










截面 A-A

NOTES:

1. CURRENT RATING:
3.0A MAX.
2. DIELECTRIC WITHSTAND VOLTAGE:
100VAC.
3. TEMPERATURE RANGE:
-30 °C ~ 85 °C.
4. CONTACT RESISTANCE:
40 MILLIONHM MAX.
5. INSULATION RESISTANCE:
100 MEGOHMS MIN.
6. INSERTION FORCE :
5N~20N.
7. UNMATING FORCE:
8N~20N.
8. DURABILITY:
10,000 CYCLES.
9. ALL PRODUCTS COMPLY WITH RoHS
ENVIRONMENTAL REQUIREMENTS.
- 10: MARK "▼" AS THE FOCUS,
FIRST ITEM INSPECTION.
- 11: MARK "⊗" TO MEASURE DIMENSIONS
FOR FAI.

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND	TX1+	TX1-	VBUS	CC1	D+	D-	SBU1	VBUS	RX2-	RX2+	GND
GND	RX1+	RX1-	VBUS	SBU2	D-	D+	CC2	VBUS	TX2-	TX2+	GND
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1

TABLE:

P/N	PART NAME	MATERIALS	FINISH
	SHELL	Stainless Steel,T=0.15mm;	Ni:50u"Min
	LATCH	Stainless Steel,T=0.3mm;	Electroplated semi-nickel matte tin;50u"Min;
	EMC SPRING	Stainless Steel,T=0.10mm	-----
	CONTACT	Copper Alloy,T=0.20mm	Ni:50u"Min; Au:CONTACT AREA:1u", Solder AREA:Sn 50-100u"
	PLASTIC	LCP(G.F30%) BLACK.	-----




深圳市华宇创精密电子有限公司


TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2" X.X' ±0.5'	DRAWN BY : Miles	DATE : 2025-11-17	PART NAME: USB TYPE C 公头24P 铆合壳 外壳夹板式带K脚
	CHECKED BY: Miles	DATE : 2025-11-17	PART NO. HYC673-USBC24-130
	APPROVED BY: G. Q. L.	DATE : 2025-11-17	MOLD NO. DRAW NO: HYC-2601071020
SCALE:1:1	SIZE: A4		SHEET NO. 1 OF 2

RECOMMENDED PCB LAYOUT
PCB THICKNESS 0.8mm
GENERAL TOLERANCE ±0.05


包装示意图:




每袋500PCS



热封线



每卷包500PCS, 每箱装20袋 (10000PCS)




产品外标签

备注:

1. 将产品装入PE袋中, 每袋装500PCS, 装完成后需用热熔机封口.
2. 在每袋装OK的PE袋上, 贴上物料和RoHS标签装入纸箱内. 每箱装20袋(10000PCS).
3. 纸箱用封箱带将其封好, 胶带要求工字型, 不可遮住标签;
4. 如果客户对包装标签另有要求, 请按客户要求作业; 有未满足之零数箱需用缓冲材料填充;



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.* ±2* X.X* ±0.5*  UNIT: mm [inch] SCALE:1:1 SIZE: A4	DRAWN BY : Miles	DATE : 2025-11-17	PART NAME: 包装图	
	CHECKED BY: Miles	DATE : 2025-11-17	PART NO.	
	APPROVED BY: G. Q. L	DATE : 2025-11-17	DRAW NO:	
			SHEET NO.	2 OF 2