



PCB板安装孔图

主要技术特性要求:

1. 使用条件:  
 环境温度: -25~+70℃  
 相对湿度: 95% (40℃)
2. 额定负荷: 2A 12V DC
3. 接触电阻: ≤30mΩ
4. 绝缘电阻: ≥100MΩ
5. 耐压: 250V AC (50Hz) 1min
6. 插拔力: 5-50N
7. 寿命: ≥5000次

序号	名称	数量	材料	处理	单件质量	总计质量	备注
7	斜针	1	黄铜0.28mm	D. Cu/Sn			
6	左长针	1	黄铜0.35mm	D. Cu/Sn			
5	右长针	1	黄铜0.35mm	D. Cu/Sn			
4	右短针	1	黄铜0.35mm	D. Cu/Sn			
3	左短针	1	黄铜0.35mm	D. Cu/Sn			
2	包圆	1	黄铜0.25mm	D. Cu/Sn			
1	基座	1	PBT				



**深圳市华宇创精密电子有限公司**

<b>TOLERANCE:</b> X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'		<b>DRAWN BY :</b> 陈一鸣	<b>DATE :</b> 2014-02-23	<b>PART NAME:</b> MDC 插头	
<b>UNIT: mm [inch]</b> SCALE:1:1 SIZE: A4		<b>CHECKED BY:</b> 马跃	<b>DATE :</b> 2014-02-23	<b>PART NO.</b> HYC-MDC-412	<b>MOLD NO.</b> /
		<b>APPROVED BY:</b> 邱敏	<b>DATE :</b> 2014-02-23	<b>DRAW NO:</b> HYC-2511211108	<b>SHEET NO.</b> 1 OF 1