


Pin Assignments			
Shell	Shield		
10	MicB_SSRX+	3	D+
9	MicB_SSRX-	2	D-
8	GND_DRAIN	1	VBUS
7	MicB_SSTX+		
6	MicB_SSTX-		
5	GND		
4	ID		
ITEM	DESCRIPTION	PIN NO.	SIGNAL NAME

3	CONTACT	3	D+
2	SHELL	2	D-
1	HOUSING	1	VBUS
ITEM	DESCRIPTION	PIN NO.	SIGNAL NAME

NOTE:

- MATERIAL:
HOUSING: LCP WITH 30% GF, UL 94V-0, BLACK COLOR.
CONTACTS: BRASS.
SHELL: STAINLESS STEEL.
- FINISH:
CONTACTS: GOLD FLASH PLATED ON CONTACT AREA, [100μ"] MIN..
BRIGHT-TIN ON SOLDER TAIL, WITH ENTIRE CONTACT UNDERPLATED [50μ"] MIN.. NICKEL.
SHELL: [50μ"] MIN. NICKEL UNDERPLATING OVER ALL.



RECOMMENDED PCB LAYOUT



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: MICRO USB 3.0 插板12.55
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC21-USBD10-125
	APPROVED BY: 邱敏	DATE : 2014-02-23	MOLD NO.
UNIT: mm [inch] SCALE:1:1 SIZE: A4			DRAW NO: HYC-2502101859
			SHEET NO. 1 OF 1