



RECOMMENDED PCB LAYOUT(TOP VIEW)  
GENERAL TOLERANCES:±0.05

SPECIFICATION:

1. CURRENT RATING: 0.5A(2.3.4CONTACT)/1.8A(1.5CONTACT) MAX.
2. VOLTAGE: 30 VAC
3. TEMPERATURE RANGE: -30 度 ~ 85 度
4. CONTACT RESISTANCE: 30 MILLIONHM MAX.
5. DIELECTRIC WITHSTANDING VOLTAGE: 250 VAC r.m.s
6. INSULATION RESISTNACE: 100 MEGOHMS MIN.

NO.	DESCRIPTION	MATERIAL	REMARKS	QTY
3	CONTACT	COPPER ALLOY T=0.15mm	Au1u"&5u"/Ni Plated	1PCS
2	HOUSING	High temperature plastic	BLACK	1SET
1	SHELL	STAINLESS STEEL T=0.30mm	MATTE TIN/Ni Plated	1PCS



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: MICRO USB 5P 小牛角无卷边(内插7.2)
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. : HVC300-USBD05-720
 UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	MOLD NO. : /
			DRAW NO. : HVC-21111610213
			SHEET NO. : 1 OF 1