


Specification:

- Contact Resistance: 35 m Ohm Max.
- Insulation Resistance: 200 M Ohm Min. At 500V DC.
- Contact Current Rating: 1 Amp AC/DC
- Voltage Rating: 40V AC.
- Withstanding Voltage: 500V AC For 1 Minute.
- Operating Temperature: -25°C to +85°C
- Packing: Tray
- Control Dimensions Indicated From "▲".

Material and Finish:

- Insulator Material: PBTUL94-V0,Black
- Cover Material: PBTUL94-V0,Black
- Hood Plastic Material: ABS,Black
- Bullon Plastic Material: ABS,Black
- Contact Material: Phosphor Bronze(C5191-EH)T=0.25
- Contact Area Plated: Gold 1~30u" Plated Over Nickel 50u".
- Solder Area Plated: Tin Plated(80u" min Lead Free)
- Up or Down Shell Material: SPCC T=0.50
- Up or Down Shell Plated: Nickel 80u" Plated Over Cu 50u"
- Connector Shell Material: SPCC T=0.50
- Connector Shell Plated: Gold 1~3u" Plated Over Cu 50u"
- Hook Spring Material: Stainless Steel T=0.30



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.' ±2" X.X' ±0.5"	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: SCSI HPCN 50P Solder-type Male	
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC68-SCSI150-388	MOLD NO.
UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HYC-2309050957	SHEET NO. 1 OF 1