


P. C. B EDGE



NOTE:

- 1.MATERIAL:
 - a.HOUSING:THERMOPLASTIC GLASS FIBRE UL94V-0
 - b.CONTACT:BRASS T=0.20mm
(SURFACE PLATING: Au*u”+Sn100u”+Ni50u”Min)
SEE ORDERING INFORMATION
 - c.CRUST: T=0.30mm
(SURFACE PLATING:Ni80u”Min)
SEE ORDERING INFORMATION
- 2.ELECTRIC:
 - a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
 - b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
 - c.DIELECTNIC VOLTAGE: 500V AC ONE SEC LEVEL
 - d.OPERATING TEMPERATURE: -55° C~ +85° C



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: USB AF 全贴片 1.0柱 无卷边
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC330-USB A04-100
UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	MOLD NO.
			DRAW NO: HYC-2503111143
			SHEET NO. 1 OF 1