



X (颜色)
黑/black (B)
蓝/blue (BL)

铆合	HYC108-VGA15B-038-X
铆合附螺丝	HYC108-VGA15B-038-F-X

NOTE:

- MATERIAL:
 - INSULATOR:PBT+30%GF, UL94V-0, COLOR:BLUE
 - COVER:PBT+30%GF, UL94V-0, COLOR:BLUE
 - CONTACT: COPPER ALLOY.
 - SHELL:SPCC
 - SQUARE RIVET:BRASS
 - GROUND HARPOON:SPCC
- PLATING:
 - CONTACT:SELECTIVE GOLD PLATED ON CONTACT AREA
80u" Min. TIN PLATED ON SOLDER TAIL
50u" Min. NICKEL UNDER-PLATED
 - SHELL:NICKEL PLATED OVERALL
 - SQUARE RIVET:TIN PLATED OVERALL
 - GROUND HARPOON:TIN PLATED OVERALL
- SPECIFICATIONS:

VOLTAGE: 250 VAC(RMS) MAX.
CURRENT RATING: 3 AMPERE PER CONTACT
CONTACT RESISTANCE: 30 MILLIOHMS MAX.
INSULATION RESISTANCE: 1000 MEGOHMS MIN.
DIELECTRIC WITHSTANDING VOLTAGE: 500V AC(RMS)
MATING FORCE: 5.1Kg.Max.
UNMATING FORCE: 1.0-4.0Kg.Min.
OPERATING TEMPERATURE:-25°C ~ +85°C
- DESIGN STANDARD ACCORDING TO D-SUB SPECIFICATION.



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: VGA 3.08 母座铆合	
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO.	SEE TABLE
UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 柯南	DATE : 2014-02-23	DRAW NO:	HYC-1912061928
			SHEET NO.	1 OF 1