



X(材质)	X(电镀)
铜壳 (C)	金/Gold(G)
铁壳 (I)	镍/Nickel(N)

NOTE :

1. SPECIFICATION:

- 1.1. CURRENT RATING: 0.5 Amp Max.
- 1.2. VOLTAGE RATING: 40 V ac(r.m.s) Max.
- 1.3. CONTACT RESISTANCE: 10m ohms Max.mated
- 1.4. INSULATION RESISTANCE:100M ohms Min.
- 1.5. DIELECTRIC WITHSTANDING VOLTAGE:
AC 500V Min. (for 1 minute)

1.6. OPERATION TEMPERATURE RANGE:-25° C~85° C

2. MECHANICAL

- 2.1. INSERTION FORCE:4.5KGF MAXMUM
- 2.1. WITHDRAWAL FORCE:1.0KGF MINIMUM;4.0KGF MAXMUM
- 2.3. DURABILITY:10000 CYCLES AT 100±50 CYCLES PERHOUR, CONTACT CHANCE FROM INITIAL VALUE:30MINI Ohms MAX

”▲ ”为品管重点管控尺寸

 深圳市华宇创精密电子有限公司			
TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.' ±2' X.X' ±0.5'	DRAWN BY :	DATE :	PART NAME:
	陈一鸣	2014-02-23	HDMI A TYPE 公座夹板 1.2
UNIT: mm [inch] SCALE:1:1 SIZE: A4	CHECKED BY:	DATE :	PART NO.
	马跃	2014-02-23	HVC125-HDMI A19-120-XX
	APPROVED BY:	DATE :	DRAW NO:
	邱敏	2014-02-23	HVC-HDMI201217301
			SHEET NO. 1 OF 1