



PCB 焊盘区
RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ±0.05



PIN NO.	PIN NAME
C1	VCC
C2	RST
C3	CLK
C5	GND
C6	VPP
C7	I/O

Specification

MATERIAL:

Insulator: High Temperature Thermoplastic, UL 94V-0.
Contact: Copper Alloy
SHELL: SUS

PLATING:

Contact: Plated 50u'' Ni Overall Contact Au 1u, Pad Au 0.8u
Shell: clean

Electrical:

Current Rating :0.5Amps max
Voltage Rating :5V AC/DC
Ambient Temperature Range :-40° C~+85° C
Storage Temperature Range :-40° C~+85° C
Ambient Humidity Range :95% R.H. Max.
Contact Resistance:80m Ωmax.
Insulation Resistance:100M Ωmin./100V DC
Mating Cycles:5,000 Insertions
Reflow peak temp. : 260° C ±5° C, 3~5 S



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: MICRO SIM 6P 掀盖1.5H
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HVC374-SIM06-155
 UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	PART NO. HVC374-SIM06-155
			DRAW NO: HVC-2601221601
			SHEET NO. 1 OF 1