





SPECIFICATIONS

- 1、Current Rating: 2A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material: Wafer PA6T, UL94V-0
PIN Brass Tin-plated
Solder tad Brass Tin-plated



PIN	尺寸 (mm)			
	A	B	C	D
02	2.00	8.00	6.50	5.00
03	4.00	10.00	8.50	7.00
04	6.00	12.00	10.50	9.00
05	8.00	14.00	12.50	11.00
06	10.00	16.00	14.50	13.00
07	12.00	18.00	16.50	15.00
08	14.00	20.00	18.50	17.00
09	16.00	22.00	20.50	19.00
10	18.00	24.00	22.50	21.00
11	20.00	26.00	24.50	23.00
12	22.00	28.00	26.50	25.00
13	24.00	30.00	28.50	27.00
14	26.00	32.00	30.50	29.00
15	28.00	34.00	32.50	31.00
16	30.00	36.00	34.50	33.00

PCB LAYOUT



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: PH 立贴
	CHECKED BY : 马跃	DATE : 2014-02-23	PART NO. : HYC15-LFN-200
UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY : 邱国夷	DATE : 2014-02-23	DRAW NO. : HYC-2601231620
			SHEET NO. : 1 OF 1