



PCB LAYOUT

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
2X04P	3.00	7.10
2X05P	4.00	8.10
2X06P	5.00	9.10
2X07P	6.00	10.10
2X08P	7.00	11.10
2X10P	9.00	13.10
2X12P	11.00	15.10
2X15P	14.00	18.10
2X20P	19.00	23.10

SPECIFICATIONS

Current Rating: 1A AC,DC
 Voltage Rating: 50V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 100MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Pin Material: Phosphor Bronze/Gold-flash
 Solder Tabs: Phosphor Bronze/Gold-flash
 Material: LCP OR PA6T,UL94V-0
 Color: Natural(Beige)



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: 1.0PH 线对板插座 卧贴
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC68-WF2XN-100
UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	MOLD NO.
			DRAW NO: HYC-2601300940
			SHEET NO. 1 OF 1