



Notes:

- Material:
 - Insulator : Thermoplastic G.F. UL94V-0,BULE
 - Contacts : Copper Alloy
 - Shell : SPCC
- Environmental :
 - 55°C to +105°C
- Electrical
 - Voltage : 30VAC(R.M.S)
 - Current Rating : 1.5 Ampere Min.
 - Contact resistance : 30 Milliohms Max.
 - Insulation resistance : 100 Megohms Min.
 - Dielectric withstanding voltage : 500 VAC
- Finish
 - Shell : 50u" min. Nickel
 - Contacts : 1~30u" min. Gold on mating area.
 - 100u" min. Tin on the tails.

3	外壳	BRASS	NICKEL PLATED
2	端子	COPPER ALLOY	GOLD/TIN PLATED
1	胶芯	HIGH TEMPERATURE PLASTIC	UL94V-0
NO.	PART NAME	MATERIAL	DESCRIPTION



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: USB 3.0 AM贴片式 沉板1.9有柱
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. : HVC51-USBA09-190
UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO. : HVC-2602021607
			SHEET NO. : 1 OF 1