



主要技术特性要求:

1. 使用条件:

环境温度:  $-25\sim 70^{\circ}$

相对湿度: 95% ( $40^{\circ}$ )

2. 额定负荷: 100V AC 2A

3. 接触电阻:  $\leq 30m\Omega$

4. 绝缘电阻:  $\geq 100M\Omega$

5. 耐压: 500V AC (50Hz) 1min

6. 插拔力: 20-60N

7. 寿命: 5000次

4	弹片	1	磷铜=0.2mm	D. Ni/Sn			
3	铜套	1	黄铜=0.35mm	D. Ni			
2	插针	5	黄铜=0.6mm	D. Ni/Sn			
1	基座	1	PBT				
序号	名称	数量	材料	处理	单件质量	总计质量	备注



深圳市华宇创精密电子有限公司

TOLERANCE:

X.X  $\pm 0.30$

X.XX  $\pm 0.25$

X.XXX  $\pm 0.15$

X'  $\pm 2'$  X.X'  $\pm 0.5'$

UNIT: mm [inch]

SCALE: 1:1 SIZE: A4

DRAWN BY:

陈一鸣

DATE:

2014-02-23

PART NAME:

DSCT插头(母头)

CHECKED BY:

马跃

DATE:

2014-02-23

PART NO.

HYC-DSCT-507M-08

MOLD NO.

APPROVED BY:

邱敏

DATE:

2014-02-23

DRAW NO:

HYC-2312211701

SHEET NO.

1 OF 1