



1. 材质和电镀:
 - 1.1 端子: 不锈钢T=0.10mm, 弹片和焊脚刷金G/F
 - 1.2 塑胶: LCP UL94V-0
2. 正向应力: 30gf MIN, 10000次以上
3. 电气性能:
 - 3.1 额定电流: 1A MAX
 - 3.2 额定电压: 12V AC (RMS)
 - 3.3 耐电压: 100 V AC FOR 1 MINUTE
 - 3.4 绝缘阻抗: 100 MEGAOHMS MIN
 - 3.5 接触阻抗: 50 MILLIOHMS MAX

P.C.BLAYEOUT
TOLERANCE: ± 0.05



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ± 0.30 X.XX ± 0.25 X.XXX ± 0.15 X' $\pm 2'$ X.X' $\pm 0.5'$	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: 电池弹片 2PIN 4.7H 中心柱
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HVC-TXT682547B
UNIT: mm [inch] SCALE: 1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HVC-2603131115
			SHEET NO. 1 OF 1