



RECOMMENDED PCB LAYOUT
TOP VIEW (.XX±0.05)

PART NO.	DIM A	DIM B
HYC-BA3P2517T	1.7	3.05±0.2
HYC-BA3P2520T	2.0	3.35±0.2

性能:

- 额定电流: 2.0A
- 额定电压: 12V
- 耐电压: 500V
- 接触电阻: 30mΩ
- 绝缘电阻: 500MΩ
- 工作温度: -40℃~+85℃
- 使用寿命: 5000次以上
- 塑件(材质): LCP(黑色) UL94-V0
- 接触点(材质): 锡磷青铜, 触点镀金3U", 焊脚镀金1U", 镍30-80U"
- 固定片(材质): 黄铜C2680, 镀全雾锡70U"以上, 镍底30-80U"
- 环保要求: 符合ROHS限值。



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: 2.5PH 3P 正压电池座	
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. SEE TABLE	MOLD NO.
 UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HYC-2604091201	SHEET NO. 1 OF 1