



RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ± 0.05



STEP 1 INSERT Micro-SIM CARD




STEP 2 PUSH THE SHELL




STEP 3 FINISH

SIM CARD	
Pin No.	NAME
C1	VCC
C2	RST
C3	CLK
C5	GND
C6	VPP
C7	I/O



NOTES:

- ELECTRICAL CHARACTERISTICS
 - CONTACT RESISTANCE: 60 Milliohms Max
 - INSULATION RESISTANCE: 1,000 Megohms Min.
 - VOLTAGE RATING: 50V.
 - CURRENT RATING: 1.0A.
- MECHANICAL CHARACTERISTICS
 - OPERATION TEMPERATURE RANGE: $-20^{\circ}\text{C}\sim+85^{\circ}\text{C}$
 - DURABILITY: 5000 CYCLES
- MATERIAL:
 - HOUSING: THERMOPLASTIC, UL 94-V0
 - TERMINAL: PHOSPHOR BRONZE, $T=0.15$
 - SHELL: STAINLESS STEEL, $T=0.20$
- FINISHED:
 - TERMINAL: Ni PLATED UNDER, 1U" Au MIN PLATED ON CONTACT AREA, Au PLATED ON SOLDER TAIL

 深圳市华宇创精密电子有限公司			
TOLERANCE: X.X ± 0.30 X.XX ± 0.25 X.XXX ± 0.15 X: $\pm 2^{\circ}$ X.X' $\pm 0.5^{\circ}$	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: NANO SIM 6P 掀盖1.5H
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC300-SIM06-150
UNIT: mm [inch]	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HYC-2604151552
SCALE: 1:1 SIZE: A4			SHEET NO. 1 OF 1