



Recommended P.C.B Layout

No:of pins	Dimension			
	DIM.A	DIM.B	DIM.C	DIM.D
03	11.65	4.00	9.15	10.25
04	13.65	6.00	11.15	12.25
05	15.65	8.00	13.15	14.25
06	17.65	10.00	15.15	16.25
07	19.65	12.00	17.15	18.25
08	21.65	14.00	19.15	20.25
09	23.65	16.00	21.15	22.25
10	25.65	18.00	23.15	24.25
11	27.65	20.00	25.15	26.25
12	29.65	22.00	27.15	28.25

NOTE:

Material

Insulator:Nylon 9T(UL94V-0)

Contact:phosphor Bronze

Contact Plated:Gold over Nickel or Tin

Specification

Current rating:5A

instant CURRENT:7A

Contact Resistance:30mΩ

Insulation Resistance:100MΩ

Dielectric Voltage:500V

Operdting Temperature:-40~105°



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: 2.0PH 刀式电池座公座
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC02-BCXX2010DW
	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HYC-2604221011
SCALE:1:1	SIZE: A4		SHEET NO. 1 OF 1