

技术要求:
 使用温度范围: -40℃~220℃
 额定负荷: DC50V 0.2A
 接触电阻: ≤0.03Ω
 绝缘电阻: ≥100MΩDC500V
 耐压: AC500V (50HZ)/min
 插拔力: 3~25N
 寿命: 5000次

| Color | | SCHEMATIC DIAGRAM |
|-------|---|-------------------|
| A | B | |
| 白 | 白 | |
| C | D | |
| 红 | 红 | |

| 5 | 插针 | 4 | 0.35 铁 |
|----|------|----|--------|
| 4 | 眼镜圈 | 2 | PBT |
| 3 | 垫片籽 | 4 | PBT |
| 2 | 铜套 | 2 | 0.35黄铜 |
| 1 | 底座 | 1 | PBT |
| 序号 | 部件名称 | 数量 | 材料 |




深圳市华宇创精密电子有限公司

TOLERANCE:

X.X ±0.30
 X.XX ±0.25
 X.XXX ±0.15

X' ±2' X.X' ±0.5'



UNIT: mm [inch]

SCALE:1:1 SIZE: A4

DRAWN BY :

陈一鸣

DATE :

2014-02-23

PART NAME:

AV插座

CHECKED BY:

马跃

DATE :

2014-02-23

PART NO.

HYC-AV4-8.4-10

MOLD NO.

APPROVED BY:

邱敏

DATE :

2014-02-23

DRAW NO:

HYC-2208021722

SHEET NO.

1 OF 1