



RECOMMENDED P.C.B LAYOUT(PCB THICKNESS: 1.6mm)
COMPONENT SIDE VIEW(TOLERANCE: ±0.05)

- MATERIAL&PLATING:
 - INSULATOR: SEE ORDER INFORMATION, 30%G.F, UL94V-0
INSULATOR COLOR: SEE TABLE
 - CONTACT: BRASS, GOLD FLASH PLATED IN CONTACT AREA, 80u" MIN TIN PLATED IN SOLDER AREA, 30u" MIN. NICKEL UNDERPLATED OVERALL.
 - SHELL: SPCC, NICKEL PLATED OVERALL.
 - BOARD LOCK: SPCC, TIN PLATED.
 - RIVET: COPPER ALLOY, 30u" MIN. NICKEL UNDERPLATED OVERALL.
 - SCREWLOCK: STEEL, NICKEL PLATED OVERALL.
- SPECIFICATION:
 - CURRENT RATING: 1.0A.
 - CONTACT RESISTANCE: 30mΩ MAX.
 - INSULATION RESISTANCE: 1000MΩ Min.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V PER MINUTE.
- NOTES:
 - ALL COMPONENTS ARE RoHS COMPLIANT.
 - RESISTANCE TO SOLDERING HEAT: 265°C FOR 5 SECONDS, AND ONLY FOR WAVE SOLDERING PROCESS.



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: SLIM 1.0 直鱼叉 前8后7
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC175-VGA15B-100
 UNIT: mm [inch]	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HYC-2208301548
SCALE:1:1	SIZE: A4	/	SHEET NO. 1 OF 1