



RECOMMEND P.C.B LAYOUT
BOTTOM VIEW

A放大: 4:1

1. MATERIAL&PLATING:

- 1.1 INSULATOR: SEE ORDER INFORMATION, 30%G.F, UL94V-0
INSULATOR COLOR: BLUE(300C)
- 1.2 CONTACT: BRASS, GOLD FLASH PLATED IN CONTACT AREA,
80u" MIN TIN PLATED IN SOLDER AREA,
30u" MIN. NICKEL UNDERPLATED OVERALL.
- 1.3 SHELL: SPCC, NICKEL PLATED OVERALL.
- 1.4 BOARD LOCK: SPCC, TIN PLATED.
- 1.5 RIVET: COPPER ALLOY, 30u" MIN. NICKEL UNDERPLATED OVERALL.
- 1.6 SCREWLOCK: STEEL, NICKEL PLATED OVERALL.

2. SPECIFICATION:

- 2.1 CURRENT RATING: 1.0A.
- 2.2 CONTACT RESISTANCE: 25m Ω MAX.
- 2.3 INSULATION RESISTANCE: 1000MQ Min.
- 2.4 DIELECTRIC WITHSTANDING VOLTAGE: 500V PER MINUTE.

3. NOTES:

- 3.1 ALL COMPONENTS ARE RoHS COMPLIANT.
- 3.2 RESISTANCE TO SOLDERING HEAT: 265°C FOR 5 SECONDS,
AND ONLY FOR WAVE SOLDERING PROCESS.



深圳市华宇创精密电子有限公司

TOLERANCE: X.X \pm 0.30 X.XX \pm 0.25 X.XXX \pm 0.15 X: \pm 2' X.X' \pm 0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: SLIM 1.0母座 直鱼叉 前7后8
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC144-VGA15B-100
UNIT: mm [inch]	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HYC-2111091107
SCALE: 1:1 SIZE: A4			SHEET NO. 1 OF 1