



RECOMMENDED P.C.B LAYOUT(PCB THICKNESS: 1.6mm)
COMPONENT SIDE VIEW(TOLERANCE: ±0.05)

1. MATERIAL&PLATING:

- 1.1 INSULATOR: SEE ORDER INFORMATION, UL94V-0
INSULATOR COLOR: SEE ORDER INFORMATION.
- 1.2 CONTACT: BRASS, GOLD FLASH PLATED IN CONTACT AREA,
80u"MIN TIN PLATED IN SOLDER AREA,
30u"MIN NICKEL UNDERPLATED OVERALL.
- 1.3 SHELL: SPCC, NICKEL PLATED OVERALL.
- 1.4 BOARD LOCK: SPCC, TIN PLATED OVER NICKEL UNDERPLATED OVERALL.
- 1.5 REVJET: BRASS, 30u"MIN NICKEL PLATED OVERALL.
- 1.6 SCREW: STEEL, NICKEL PLATED OVERALL.

2. SPECIFICATION:

- 2.2 CURRENT RATING: 1.0A.
- 2.3 CONTACT RESISTANCE: 25mΩ MAX.
- 2.4 INSULATION RESISTANCE: 1000MΩ MIN.
- 2.5 DIELECTRIC WITHSTANDING VOLTAGE: 500V PER MINUTE.
- 2.6 OPERATING TEMPERATURE: -20°C~+85°C

3. NOTES:

- 3.1 ALL COMPONENTS ARE RoHS COMPLIANT.
- 3.2 RESISTANCE TO SOLDERING HEAT: 265°C FOR 5 SECONDS,
AND ONLY FOR WAVE SOLDERING PROCESS.



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: SLIM2.0 15P 母座侧鱼叉 前8后7
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC226-VGA15B-200
UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HYC-2411141445
			SHEET NO. 1 OF 1