



RECOMMENDED P.C.B. LAYOUT
GENERAL TOLERANCE: ±0.05

说明:

1. 材质:

胶芯: LCP, UL94V-0; COLOR; BLACK
端子: C5191

2. 电镀说明:

端子: 接触区域镀金15U
焊锡区域镀锡
全部区域镍底

3. 性能说明:

- 1) 额定电压: $\geq 120\text{VAC RMS}$.
- 2) 额定电流: $\geq 1.5\text{AMP}$
- 3) 接触电阻: $\leq 40\text{m}\Omega$ Max.
- 4) 绝缘电阻: $\geq 500\text{M}\Omega$ MIN.
- 5) 工作温度: $-40^\circ\text{C TO } +80^\circ\text{C}$.



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: SPF CAGE 1X1 20PIN	
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC10-SPF-960	MOLD NO.
UNIT: mm [inch] SCALE: 1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HYC-2605081021	SHEET NO. 1 OF 1