



RECOMMENDED PCB LAYOUT THICKNESS=1.6mm  
TOLERANCE:±0.05

DIM A	DIM B
15.88	28.43
19.05	21.60

NOTE:

- MATERIALS AND FINISHED  
INSULATOR : PBT+30% GF UL 94V-0,  
SHELL : STEEL, NI FINISHED  
CONTACT MATERIAL:BRASS, SELEVITE GOLD FINISHED  
HARPOON:BRASS,SN FINISHED  
SCREW:COPPER ALLOY ,NI FINISHED  
WITH #4-40 THREADED ASSEMBLED
- ELECTRICAL CHARACTERISTICS  
CURRENT RATING : 1.0 AMP DC  
VOLTAGE RATING: 300 V DC  
CONTACT RESISTANCE :20 MILLIOHMS MAX.  
DIELECTRIC WITHSTANDING VOLTAGE : 100 V AC MIN.  
INSULATION RESISTANCE : 5000 MEGAOHMS MIN.
- ENVIRONMENTAL  
OPERATING TEMPERATURE: -55°C ~ +85°C  
STORAGE TEMPERATURE:-55°C ~ +105°C



深圳市华宇创精密电子有限公司

<b>TOLERANCE:</b> X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	<b>DRAWN BY :</b> 陈一鸣	<b>DATE :</b> 2014-02-23	<b>PART NAME:</b> DR37母 对 DR37母 铆锁
	<b>CHECKED BY:</b> 马跃	<b>DATE :</b> 2014-02-23	<b>PART NO.</b> HVC254-VGA74B-XXX
 UNIT: mm [inch]	<b>APPROVED BY:</b> 邱敏	<b>DATE :</b> 2014-02-23	<b>DRAW NO:</b> HVC-2605121022
	<b>SCALE:1:1</b>	<b>SIZE: A4</b>	<b>SHEET NO.</b> 1 OF 1