

X (塑胶材质)	X (材质)	X (颜色)
LCP (L)	不锈钢 (S)	黑/black (B)
PBT (P)	铜壳 (C)	白/white (W)
	铁壳 (I)	灰/gray (G)

规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN


物理性能: Mechanical:

1. 插拔力: Connector Mate and Unmate Force
Mate force: 3.57kgf (MAX)
Unmate force: 1.02kgf (MIN)
2. 端子保持力: Terminal Retention
1.0kgf (MIN)


原材料: Material:

1. 塑胶: Housing:
Hing Temperature Thermoplastics,
PBT White/Black
2. 端子: Contact: Copper Alloy C2680
Plated Gold in Mating Area;
Tin On Solder Talls
3. 外壳: Shell: Copper Alloy SPCC
Nickel Plating

5	SHELL-B	Fe	T=0.30	N i80- 100U"	1
4	SHELL-A	Fe	T=0.30	N i80- 100U"	1
3	TERMINAL-B	BRASS	T=0.25	Sn 100U"+ Au 1U"	4
2	TERMINAL-A	BRASS	T=0.25	Sn 100U"+ Au 1U"	4
1	HOUSING	PBT		WHITE/BLACK	1
NO.	Part Name	MATERIAL	THICK	FINISH	Q' TY



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: USB AF 双层弯脚 有边有后盖
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. : HVC41-USBA08-175-XX
 UNIT: mm [inch] SCALE: 1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO. : HVC-22080622
			SHEET NO. : 1 OF 1