

备注:

1. 材质:

1.1 胶芯: LCP UL94V-0

1.2 端子: C5191, 镍底50μM, 镀金1μM或3μM

1.3 外壳: C2680, 镍底50μM, 镀雾锡80μM以上或外壳镀全镍80μM以上

2. 主要特性:

2.1 额定电流: 1.0A

2.2 接触阻抗: 50mΩ MAX

2.3 绝缘阻抗: 100MΩ MIN 100V DC

2.4 耐压测试: 100V AC

2.5 沾锡性: 温度235 ± 5℃, 时间5 ± 0.5s

2.6 整体插入力: 3.57kgf MAX 整体拔出力: 0.71kgf MIN

2.7 使用寿命: 5000次

2.8 耐温性: 烤箱测试: 温度250 ± 5℃, 时间2分钟

2.9 工作环境: 温度: -30℃ ~ +80℃; 湿度: 80% MAX

3. 圆圈标记尺寸表示重点检验尺寸, CPK值不小于1.33.



深圳市华宇创精密电子有限公司


TOLERANCE:

X.X ±0.30

X.XX ±0.25

X.XXX ±0.15

X' ±2' X.X' ±0.5'



UNIT: mm [inch]

SCALE:1:1 SIZE: A4

DRAWN BY :

陈一鸣

DATE :

2014-02-23

PART NAME:

MINI USB 10PIN 沉板1.0 SMT

CHECKED BY:

马跃

DATE :

2014-02-23

PART NO.

HYC64-USBC10-100

MOLD NO.

APPROVED BY:

邱敏

DATE :

2014-02-23

DRAW NO:

HYC-2606021052

SHEET NO.

1 OF 1