

线路板安装孔位置尺寸

产品型号	六方孔径尺寸(X)	齿轮颜色
6.5A	1.69±0.02	白色
6.5B	1.72±0.02	黑色
6.5C	1.74±0.02	黑色
6.5D	1.78±0.02	黄色
6.5E	1.76±0.02	红色

产品规格参数


额定负荷	DC 5V 0.5mA	适用温度	-25℃ -- +85℃	执子数	24点执子
机械寿命	200000cycles Min	适用湿度	≤85% +40℃	分解能	各相12脉冲/360°
电气寿命	100000cycles Min	耐焊接热	260±5℃ 3S	操作力	30±15gf.cm
绝缘电阻	>50MΩ DC50V 60S	接触电阻	≤10Ω		
耐压	AC50V 60S	可焊性	235±5℃ 3S		



深圳市华宇创精密电子有限公司

TOLERANCE:

X.X ±0.30  
X.XX ±0.25  
X.XXX ±0.15  
X' ±2' X.X' ±0.5'



UNIT: mm [inch]

SCALE:1:1 SIZE: A4

DRAWN BY :

陈一鸣

DATE :

2014-02-23

PART NAME:

编码器 贴片

CHECKED BY:

马跃

DATE :

2014-02-23

PART NO.

HYC04-6.5X-5P-S

MOLD NO.

APPROVED BY:

邱敏

DATE :

2014-02-23

DRAW NO:

HYC-2607031647

SHEET NO.

1 OF 1