

NOTE:

1. MATERIAL:

1.1 HOUSING: PA9T, UL 94V-0

1.2 TERMINAL: C2680

2. FINISH:

2.1 TERMINAL: NICKEL 50 μ M MIN UNDER PLATED
OVERALL, Au PLATED ON THE CONTACT AREA.
OR Tin ON THE SOLDERING AREA.

3. PRODUCT SPECIFICATION

3.1 CURRENT RATING :5A

3.2 VOLTAGE RATING : 30V AC

3.3 DIELECTRIC WITHSTANDING VOLTAGE:500VAC

3.4 INSULATION RESISTANCE:100M Ω min.3.5 CONTACT RESISTANCE: 30m Ω Max.3.6 Operating Temperature:40 $^{\circ}$ ~105 $^{\circ}$

No:of pins	Dimension		
	DIM.A	DIM.B	DIM.C
03	9.50	8.00	5.00
04	12.00	10.50	7.50
05	14.50	13.00	10.00
06	17.00	15.50	12.50
07	19.50	18.00	15.00
08	22.00	20.50	17.50
09	24.50	23.00	20.00
10	27.00	25.50	22.50
11	29.50	28.00	25.00
12	32.00	30.50	27.50
13	34.50	33.00	30.00
14	37.00	35.50	32.50
15	39.50	38.00	35.00
16	42.00	40.50	37.50



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ± 0.30 X.XX ± 0.25 X.XXX ± 0.15 X." $\pm 2^{\circ}$ X.X" $\pm 0.5^{\circ}$	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: 2.5PH 立贴刀式电池座公座	
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC-BCXX2572EFD	MOLD NO.
 UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HYC-2609101543	SHEET NO. 1 OF 1

