






3D VIEW





SCHEMATIC



NOTES:

1. CONTACT CURRENT RATING:1A;
2. CONTACT RESISTANCE:50mΩ MAX;
3. INSULATION RESISTANCE:100MΩ MIN;
4. DIELECTRIC WITHSTANDING:500V AC MIN;
5. DURABILITY:5000CYCLES MIN;
6. CONNECTOR MATING FORCES:2.94~29.4N(0.3~3.0kgf);
7. CONNECTOR UNMATING FORCES:2.94~29.4N(0.3~3.0kgf);

P.C.B LAYOUT
TOP VIEW

(ø3.50mm 4 POLE PLUG DETAIL DRAWING)

ITEM	PART NAME	Q'TY	MATERIAL	DESCRIPTION
06	HOUSING	1 PCS	HIGH TEMPERATURE PLASTIC	BLACK,
05	CONTACT E	1 PCS	STAINLESS STEEL, T=0.20	Matte Tin
04	CONTACT C	1 PCS	PHOSPHOR BRONZE, T=0.20	Matte Tin
03	CONTACT B	1 PCS	PHOSPHOR BRONZE, T=0.20	Matte Tin
02	CONTACT B	1 PCS	PHOSPHOR BRONZE, T=0.20	Matte Tin
01	CONTACT A	1 PCS	PHOSPHOR BRONZE, T=0.20	Matte Tin



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2" X.X' ±0.5" UNIT: mm [inch] SCALE:1:1 SIZE: A4	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: PJ-327F 插件
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC02-PJ327F-140
	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HYC-2609211140
			SHEET NO. 1 OF 1