











RECOMMENDED PCB LAYOUT
TOLERANCE±0.05(焊盘推荐图)
(FOR REFERENCE ONLY)



METAL MASK T=0.10
TOLERANCE±0.05(钢网推荐图)
(FOR REFERENCE ONLY)



NOTES:

1:MATERIAL:

1-1:STAINLESS STEEL THICKNE=0.08mm

2:FINISH:

2-1:SEE DETAILED LIST.

3:PRODUCT SPECIFICATIONS:

3-1:RATED CURRENT:1.0A/MAX

3-2:VOLTAGE RATING:1.50V/AC/DC/MAX

3-3:CONTACT RESISTANCE:80mΩ/MAX

3-4:OPERATING TEMPERATURE:-40°C~85°C

3-5:NORMAL FORCE OF PRESS@3.10:0.40N MIN ON CONTACT POINT.

3-6:DURABILITY:1,500 CYCLES.

4:SALT SPRAY:SEE DETAILED LIST

5:PACKING SPECIFICATION:REEL&TARE

6:DIMENSIONS MARKED ◻,CPK>1.33

7:ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC;

8:COMPLIANT TO RoHS&LEAD FREE



深圳市华宇创精密电子有限公司


TOLERANCE:

X.X ±0.30

X.XX ±0.25

X.XXX ±0.15

X' ±2° X.X' ±0.5°



UNIT: mm [inch]

SCALE:1:1

SIZE: A4

DRAWN BY :

陈一鸣

DATE :

2014-02-23

PART NAME:

L3.50*W1.50*H1.40mm侧接弹片

CHECKED BY:

马跃

DATE :

2014-02-23

PART NO.

HYC-TXT351514AP

MOLD NO.

APPROVED BY:

邱敏

DATE :


2014-02-23

DRAW NO:


HYC-2609171544

SHEET NO.

1 OF 1




PULL OUT
IN THIS DIRECTION
引出方向



TOTAL
20LAYERS

PULL OUT
IN THIS DIRECTION/引出方向



⑤		ADHESIVE TAPE	
④		CARRIER TAPE	W12.0
③		TOP COVER	W7.50
②	1	LABLE	
①	1	ROLLER DISK	ø330
ITEM	QT'Y	NAME	SIZE



深圳市华宇创精密电子有限公司


TOLERANCE:

X.X ±0.30

X.XX ±0.25

X.XXX ±0.15

X.' ±2" X.X' ±0.5"



UNIT: mm [inch]

SCALE:1:1

SIZE: A4

DRAWN BY :

陈一鸣

DATE :

2014-02-23

PART NAME:

包装图

CHECKED BY:

马跃

DATE :

2014-02-23

PART NO.

MOLD NO.

APPROVED BY:

邱敏

DATE :

2014-02-23

DRAW NO:

SHEET NO.

1 OF 1