








SCHEMATIC

RECOMMENDED PCB LAYOUT (TOP VIEW)
GENERAL TOLERANCES: ± 0.05 

MALE PLUG SCHEMATIC

NOTES :

1.0) RATING :

- 1.1. VOLTAGE : 12 VDC (R.M.S.)
1.2. CURRENT : 1 AMPERE MAXIMUM PER CONTACT AT 30° T-RISE
1.3. TEMPERATURE : -25° TO +85°

2.0) ELECTRICAL CHARACTERISTIC

- 2.1. CONTACT RESISTANCE : INITIAL 50m MAX. AFTER 100m
2.2. INSULATION RESISTANCE : 100 M MIN.
2.3. DIELECTIC WITHSTANDING VOLTAGE : 500 VAC AT SEA LEVEL

3.0) MECHANICAL :

- 3.1. DURABILITY ,MINIMUM: MATED 5000 CYCLES WITHOUT DEGRADING ELECTRICAL
3.2. INITIAL:MATING FORCE: 300g~2000g.UNMATING FORCE: 200g~2000g
3.3. AFTER LIFE TESTING:MATING FORCE: 300g~2000g.UNMATING FORCE: 200g~2000g



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ± 0.30 X.XX ± 0.25 X.XXX ± 0.15 X.' $\pm 2'$ X.X' $\pm 0.5'$ UNIT: mm [inch] SCALE:1:1 SIZE: A4	DRAWN BY :	DATE :	PART NAME:	
	陈一鸣	2014-02-23	斜口耳机座 3.8H 三插两贴	
	CHECKED BY:	DATE :	PART NO.	HYC-PJ06E65-380
	马跃	2014-02-23	MOLD NO.	
	APPROVED BY:	DATE :	DRAW NO:	HYC-2610131055
	邱敏	2014-02-23	SHEET NO.	1 OF 1